

High-Energy HE1060 & HE532

Micro-joule picosecond laser systems




Key Features

- Up to 10 μ J pulse energy
- Ultra-short pulse widths down to <10ps
- Single-shot to 1MHz variable repetition rate
- Ultra-low Heat-Affected Zone
- 1064nm or 532nm wavelengths
- Designed for 24/7 operation and OEM integration
- Maintenance-free and air-cooled

Applications

- Materials processing
- Photovoltaic scribing
- Thin-film processing
- Micro-machining
- Semiconductor inspection and metrology
- Photo-acoustic spectroscopy



Versatile high-energy fiber lasers

The **HE1060** series is a range of high pulse energy ultrafast fiber lasers designed for industrial applications. Exceptional single-mode beam-quality, high peak-powers and class-leading stability enable the most demanding processes to be accomplished with this system.

The **HE532** series adds fully integrated second harmonic generation to efficiently produce 532nm output at micro-joule pulse energy.

Flexible

The integrated output modulator allows single-shot, burst-mode or continuous operation as well as pulse-to-pulse control of intensity,

Reliable

The systems are based on an inherently robust self-starting ultrafast fiber laser oscillator and high energy fiber amplifier. They are air-cooled and require no user alignment or maintenance.

Standard Specifications

	1064nm High-energy Ultrafast Laser			532nm High-energy Ultrafast Laser	
Model	HE1060-1	HE1060-5	HE1060-10	HE532-1	HE532-5
Central Wavelength	1064nm	1064nm	1064nm	532nm	532nm
Maximum Pulse Energy	>1μJ	>5μJ	>10μJ	>1μJ	>5μJ
Pulse Width	10ps	45ps	70ps	10-100ps	10-100ps
Variable Repetition Rate (user-selectable)	Single-shot to 1MHz			Single-shot to 1MHz	
Amplitude Noise	<±2%			<±2%	
M-squared	<1.3			<1.3	
Output Optic	Collimated			Collimated	
Output Polarization	Linear			Linear	
Cooling	Air-cooled			Air-cooled	
Power Consumption (max)	<250W			<250W	
Dimensions (WxLxH, mm)					
Laser Chassis	19" rack-mount			19" rack-mount	
Remote Optical Head	220 x 360 x 130			220 x 360 x 130	
Weight	<25kg			<25kg	

Custom Options:

- Wavelengths: **1030nm, 1045nm & 1053nm**
- Third Harmonic and Fourth Harmonic wavelengths
- Ultra-short femtosecond pulses (-fs Series)
- Electronically switchable wavelength
- Fixed or selectable repetition rates



**VISIBLE AND INVISIBLE
LASER RADIATION
AVOID EYE OR SKIN EXPOSURE TO
DIRECT OR SCATTERED RADIATION
CLASS 4 LASER PRODUCT**

CAUTION: THIS IS A CLASS 4 LASER PRODUCT AND USE OF CONTROLS AND ADJUSTMENTS OTHER THAN THOSE SPECIFIED IN THE PRODUCT MANUAL MAY RESULT IN HAZARDOUS LASER RADIATION EXPOSURE

Fianium UK Ltd.

20 Compass Point, Ensign Way, Southampton, SO31 4RA, UK
Tel: +44 2380 458776 Fax: +44 2380 458734 Email: info@fianium.com

Fianium US Inc.

858 West Park Street, Eugene, OR 97401, USA
Tel: 1 541 343 6767 Fax: 1 541 343 1838 Email: sales@fianium.com

Fianium Asia Ltd.

21/F, New World Tower One, 18 Queen's Road Central, Hong Kong
Tel: +852 2607 4236 Fax: +852 3013 6883 Email: asia@fianium.com